

Package: fechner (via r-universe)

May 29, 2026

Version 1.0-4

Date 2026-05-28

Title Fechnerian Scaling of Discrete Object Sets

Description Functions and example datasets for Fechnerian scaling of discrete object sets. User can compute Fechnerian distances among objects representing subjective dissimilarities, and other related information. See `package?fechner` for an overview.

Author Ali Uenlue [aut, cre], Thomas Kiefer [aut, trl] (Based on original MATLAB source by Ehtibar N. Dzhafarov.)

Maintainer Ali Uenlue <aligalibuenlue@gmail.com>

Depends R (>= 4.6.0)

Imports graphics, stats

LazyLoad yes

LazyData yes

License GPL (>= 2)

NeedsCompilation yes

Repository <https://uenlue.r-universe.dev>

Date/Publication 2026-05-28 23:50:02 UTC

RemoteUrl <https://github.com/cran/fechner>

RemoteRef HEAD

RemoteSha f05a8dd2d6ff274c368116ad30785a77b4fd3e97

Contents

fechner-package	2
check.data	3
check.regular	5
fechner	7
morse	13

noRegMin	14
plot.fechner	15
print.fechner	17
print.summary.fechner	18
regMin	19
summary.fechner	20
wish	22

Index	24
--------------	-----------

fechner-package	<i>Fechnerian Scaling of Discrete Object Sets: The R Package fechner</i>
-----------------	--

Description

Fechnerian scaling is a procedure for constructing a metric on a set of objects (e.g., symbols, X-ray films). The constructed Fechnerian metric represents subjective dissimilarities among the objects as perceived by a system (e.g., person, technical device). The package **fechner** provides functions and example datasets for performing and illustrating Fechnerian scaling of discrete object sets in R.

Details

Package: **fechner**
 Type: Package
 Version: 1.0-4
 Date: 2026-05-25
 License: GPL (>= 2)

Fechnerian scaling of discrete object (or stimulus) sets provides a theoretical framework for deriving, so-called Fechnerian, distances among objects representing subjective dissimilarities. A Fechnerian metric on a set of stimuli is constructed from the probabilities with which the objects are discriminated from each other by a perceiving system. In addition to the oriented and overall Fechnerian distances, the package **fechner** also computes such related information as the points of subjective equality, the psychometric increments, the geodesic chains and loops with their corresponding lengths, and the generalized Shepardian dissimilarities (or *S*-index). Moreover, the package **fechner** provides functions for checking the required data format and the fundamental regular minimality/maximality condition. These concepts are explained in detail in the paper about the **fechner** package by *Uenlue, Kiefer, and Dzhafarov (2009)*, and in the theoretical papers by *Dzhafarov and Colonius (2006, 2007)* (see ‘References’).

The package **fechner** is implemented based on the S3 system. It comes with a namespace, and consists of three external functions (functions the package exports): `check.data`, `check.regular`, and the main function of this package, `fechner`. It also contains six internal functions (functions not exported by the package), which are `plot`, `print`, and `summary` methods for objects of the class `fechner`, a `print` method for objects of the class `summary.fechner`, and two functions for computing intermediate graph-theoretic information: `plot.fechner`, `print.fechner`, `summary.fechner`, `print.summary.fechner`, and `fechner-internal`. The features of the package **fechner** are illustrated with accompanying two real datasets, `morse` and `wish`, and two artificial datasets, `regMin` and `noRegMin`.

Author(s)

Thomas Kiefer, Ali Uenlue. Based on original MATLAB source by Ehtibar N. Dzhafarov.

Maintainer: Ali Uenlue <aligalibuenlue@gmail.com>

References

Dzhafarov, E. N. and Colonius, H. (2006) Reconstructing distances among objects from their discriminability. *Psychometrika*, **71**, 365–386.

Dzhafarov, E. N. and Colonius, H. (2007) Dissimilarity cumulation theory and subjective metrics. *Journal of Mathematical Psychology*, **51**, 290–304.

Uenlue, A. and Kiefer, T. and Dzhafarov, E. N. (2009) Fechnerian scaling in R: The package **fechner**. *Journal of Statistical Software*, **31**(6), 1–24. URL <https://www.jstatsoft.org/article/view/v031i06>.

check.data

Check for Required Data Format

Description

check.data is used to check whether the data are of required format.

Usage

```
check.data(X, format = c("probability.different", "percent.same",  
                        "general"))
```

Arguments

X	a required square matrix or data frame of numeric data. No NA, NaN, Inf, or -Inf values are allowed.
format	an optional character string giving the data format to be checked. This must be one of "probability.different", "percent.same", or "general", with default "probability.different", and may be abbreviated to a unique prefix.

Details

The data must be a matrix or a data frame, have the same number of rows and columns, and be numeric consisting of real numbers. In particular, no infinite, undefined, or missing values are allowed. This is the general data format. The probability-different and percent-same formats, in addition, require that the data lie in the intervals $[0, 1]$ and $[0, 100]$, respectively. If all of the requirements for a data format are satisfied, the data are returned as a matrix with rows and columns labeled; otherwise the function produces respective messages.

The labeling is as follows.

1. If the data are entered without any labeling of the rows and columns: The function does the labeling automatically, as $a_1, b_1, \dots, z_1, a_2, b_2, \dots, z_2, \dots$, etc., up to a_9, b_9, \dots, z_9 if the data are as large as 234×234 , or if the data are larger than 234×234 , the labeling is v_1, v_2, \dots, v_N , where $N \times N$ is the dimension of the data (and $N > 234$).
2. If the data are entered with either row or column labeling: In that case, the row or column labels are assigned to the columns or rows, respectively.
3. If the data are entered with row and column labeling: Since the labeling of both the rows and columns is now provided by the user manually, the same labeling must be used for both. If this is the case, the labeling is adopted. Otherwise the function produces a respective message.

Value

If the data are of required format, `check.data` returns a matrix of the data with rows and columns labeled.

Author(s)

Thomas Kiefer, Ali Uenlue. Based on original MATLAB source by Ehtibar N. Dzhafarov.

References

- Dzhafarov, E. N. and Colonius, H. (2006) Reconstructing distances among objects from their discriminability. *Psychometrika*, **71**, 365–386.
- Dzhafarov, E. N. and Colonius, H. (2007) Dissimilarity cumulation theory and subjective metrics. *Journal of Mathematical Psychology*, **51**, 290–304.
- Uenlue, A. and Kiefer, T. and Dzhafarov, E. N. (2009) Fechnerian scaling in R: The package **fechner**. *Journal of Statistical Software*, **31**(6), 1–24. URL <https://www.jstatsoft.org/article/view/v031i06>.

See Also

[check.regular](#) for checking regular minimality/maximality; [fechner](#), the main function for Fechnerian scaling. See also [fechner-package](#) for general information about this package.

Examples

```
## dataset wish is of probability-different format
check.data(wish)

## dataset morse is of percent-same format
check.data(morse, format = "percent.same")

## a matrix without any labeling of rows and columns, of general format
## check.data does the labeling automatically
(X <- ((-1) * matrix(1:16, nrow = 4)))
check.data(X, format = "general")

## examples of data that are not of any of the three formats
```

```
## message: data must be matrix or data frame
check.data(as.character(matrix(1:16, nrow = 4)))

## message: data must have same number of rows and columns
check.data(matrix(1:12, nrow = 4))

## message: data must be numbers
check.data(matrix(LETTERS[1:16], nrow = 4))
```

check.regular	<i>Check for Regular Minimality/Maximality</i>
---------------	--

Description

check.regular is used to check whether the data satisfy regular minimality/maximality.

Usage

```
check.regular(X, type = c("probability.different", "percent.same",
                          "reg.minimal", "reg.maximal"))
```

Arguments

X	a required square matrix or data frame of numeric data. No NA, NaN, Inf, or -Inf values are allowed.
type	an optional character string giving the type of check to be performed. This must be one of "probability.different", "percent.same", "reg.minimal", or "reg.maximal", with default "probability.different", and may be abbreviated to a unique prefix.

Details

The type argument specifies whether regular minimality or regular maximality is to be checked. "probability.different" and "percent.same" are for datasets in the probability-different and percent-same formats, and imply regular minimality and regular maximality checks, respectively. "reg.minimal" and "reg.maximal" can be specified to force checking for regular minimality and regular maximality, respectively, independent of the used dataset. In particular, "reg.minimal" and "reg.maximal" are to be used for datasets that are properly in the general format.

check.regular calls [check.data](#). In particular, the rows and columns of the canonical representation matrix (see 'Value') are canonically relabeled based on the labeling provided by [check.data](#). That is, using the [check.data](#) labeling, the pairs of points of subjective equality (PSEs) are assigned identical labels, leaving intact the labeling of the rows and relabeling the columns with their corresponding PSEs. If the data X do not satisfy regular minimality/maximality, check.regular produces respective messages. The latter give information about parts of X violating that condition.

Regular minimality/maximality is a fundamental property of discrimination and means that

1. every row contains a single minimal/maximal entry;

2. every column contains a single minimal/maximal entry;
3. an entry p_{ij} of X which is minimal/maximal in the i th row is also minimal/maximal in the j th column, and vice versa.

If p_{ij} is the entry which is minimal/maximal in the i th row and in the j th column, the i th row object (in one, the first, observation area) and the j th column object (in the other, the second, observation area) are called each other's PSEs. In psychophysical applications, for instance, observation area refers to the two fixed and perceptually distinct areas in which the stimuli are presented pairwise; for example, spatial arrangement (left versus right) or temporal order (first versus second).

Value

If the data do satisfy regular minimality/maximality, `check.regular` returns a named list consisting of the following four components:

`canonical.representation`

a matrix giving the representation of X in which regular minimality/maximality is satisfied in the canonical form. That is, the single minimal/maximal entries of the rows and columns lie on the main diagonal (of the canonical representation). In addition, the rows and columns are canonically relabeled.

`canonical.transformation`

a data frame giving the permutation of the columns of X used to produce the canonical representation of X . The first and second variables of this data frame, `observation.area.1` and `observation.area.2`, respectively, represent the pairs of PSEs. The third variable, `common.label`, lists the identical labels assigned to the pairs of PSEs.

`check`

a character string giving the check that was performed. This is either "regular minimality" or "regular maximality".

`in.canonical.form`

logical. If TRUE, the permutation of the columns used to obtain the canonical representation of X is the identity; that is, the original data X are already in the canonical form.

Author(s)

Thomas Kiefer, Ali Uenlue. Based on original MATLAB source by Ehtibar N. Dzhafarov.

References

- Dzhafarov, E. N. and Colonius, H. (2006) Reconstructing distances among objects from their discriminability. *Psychometrika*, **71**, 365–386.
- Dzhafarov, E. N. and Colonius, H. (2007) Dissimilarity cumulation theory and subjective metrics. *Journal of Mathematical Psychology*, **51**, 290–304.
- Uenlue, A. and Kiefer, T. and Dzhafarov, E. N. (2009) Fechnerian scaling in R: The package **fechner**. *Journal of Statistical Software*, **31**(6), 1–24. URL <https://www.jstatsoft.org/article/view/v031i06>.

See Also

[check.data](#) for checking data format; [fechner](#), the main function for Fechnerian scaling. See also [fechner-package](#) for general information about this package.

Examples

```
## dataset wish satisfies regular minimality in canonical form
check.regular(wish)

## dataset regMin satisfies regular minimality in non-canonical
## form and so is canonically transformed and relabeled
regMin
check.regular(regMin)

## dataset noRegMin does satisfy neither regular minimality nor
## regular maximality
check.regular(noRegMin, type = "probability.different")
check.regular(noRegMin, type = "reg.maximal")

## dataset morse satisfies regular maximality in canonical form
check.regular(morse, type = "percent.same")
## part of morse data satisfies regular maximality
check.regular(morse[c(2, 27:36), c(2, 27:36)], type = "reg.maximal")
```

fechner

Main Function For Fechnerian Scaling

Description

fechner provides the Fechnerian scaling computations. It is the main function of this package.

Usage

```
fechner(X, format = c("probability.different", "percent.same", "general"),
        compute.all = FALSE, check.computation = FALSE)
```

Arguments

X	a required square matrix or data frame of numeric data. No NA, NaN, Inf, or -Inf values are allowed.
format	an optional character string giving the data format that is used. This must be one of "probability.different", "percent.same", or "general", with default "probability.different", and may be abbreviated to a unique prefix.
compute.all	an optional logical. The default value FALSE corresponds to short computation, which yields the main Fechnerian scaling computations. The value TRUE corresponds to long computation, which additionally yields intermediate results and also allows for a check of computations if check.computation is set TRUE.

`check.computation`

an optional logical. If TRUE, the check for whether the overall Fechnerian distance of the first kind (in the first observation area) is equal to the overall Fechnerian distance of the second kind (in the second observation area) is performed. The check requires `compute.all` to be set TRUE.

Details

The `format` argument specifies the data format that is used. `"probability.different"` and `"percent.same"` are for datasets in the probability-different and percent-same formats, and in the latter case, the data are automatically transformed prior to the analysis using the transformation $(100 - X)/100$. `"general"` is to be used for datasets that are properly in the general data format. Note that for `"percent.same"`, the data must satisfy regular maximality, for `"probability.different"` and `"general"`, regular minimality (otherwise function `fechner` produces respective messages). In particular, data in the general format may possibly need to be transformed manually prior to calling the function `fechner`.

If `compute.all = TRUE` and `check.computation = TRUE`, the performed check computes the difference 'overall Fechnerian distance of the first kind minus overall Fechnerian distance of the second kind'. By theory, this difference is zero. The function `fechner` calculates that difference and checks for equality of these Fechnerian distances up to machine precision (see 'Value'). `fechner` calls `check.regular`, which in turn calls `check.data`. In particular, the specified data format and regular minimality/maximality are checked, and the rows and columns of the canonical representation matrix (see `check.regular`) are canonically relabeled based on the labeling provided by `check.data`.

The function `fechner` returns an object of the class `fechner` (see 'Value'), for which `plot`, `print`, and `summary` methods are provided; `plot.fechner`, `print.fechner`, and `summary.fechner`, respectively. Moreover, objects of the class `fechner` are set the specific named attribute `computation`, which is assumed to have the value `short` or `long` indicating whether short computation (`compute.all = FALSE`) or long computation (`compute.all = TRUE`) was performed, respectively.

Value

If the arguments `X`, `format`, `compute.all`, and `check.computation` are of required types, `fechner` returns a named list, of the class `fechner` and with the attribute `computation`, which consists of 6 or 18 components, depending on whether short computation (`computation` is then set `short`) or long computation (`computation` is then set `long`) was performed, respectively.

The short computation list contains the following first 6 components, the long computation list the subsequent ones:

`points.of.subjective.equality`

a data frame giving the permutation of the columns of `X` used to produce the canonical representation of `X`. The first and second variables of this data frame, `observation.area.1` and `observation.area.2`, respectively, represent the pairs of points of subjective equality (PSEs). The third variable, `common.label`, lists the identical labels assigned to the pairs of PSEs. (first component of short computation list)

canonical.representation	a matrix giving the representation of X in which regular minimality/maximality is satisfied in the canonical form. That is, the single minimal/maximal entries of the rows and columns lie on the main diagonal (of the canonical representation). In addition, the rows and columns are canonically relabeled.
overall.Fechnerian.distances	a matrix of the overall Fechnerian distances (of the first kind); by theory, invariant from observation area.
geodesic.loops	a data frame of the geodesic loops of the first kind; must be read from left to right for the first kind, and from right to left for the second kind.
graph.lengths.of.geodesic.loops	a matrix of the graph-theoretic (edge/link based) lengths of the geodesic loops (of the first kind).
S.index	a matrix of the generalized ‘Shepardian’ dissimilarity (or S-index) values. An S-index value is defined as the psychometric length of the loop between a row stimulus and a column stimulus containing only these two stimuli. (last component of short computation list)
points.of.subjective.equality	the same as in case of short computation; see above. (first component of long computation list)
canonical.representation	the same as in case of short computation; see above.
psychometric.increments.1	a matrix of the psychometric increments of the first kind.
psychometric.increments.2	a matrix of the psychometric increments of the second kind.
oriented.Fechnerian.distances.1	a matrix of the oriented Fechnerian distances of the first kind.
overall.Fechnerian.distances.1	a matrix of the overall Fechnerian distances of the first kind.
oriented.Fechnerian.distances.2	a matrix of the oriented Fechnerian distances of the second kind.
overall.Fechnerian.distances.2	a matrix of the overall Fechnerian distances of the second kind.
check	if <code>check.computation = TRUE</code> , a list of two components: <code>difference</code> and <code>are.nearly.equal</code> . The component <code>difference</code> is a matrix of the differences of the overall Fechnerian distances of the first and second kind; ought to be a zero matrix. The component <code>are.nearly.equal</code> is a logical indicating whether this matrix of differences is equal to the zero matrix up to machine precision. If <code>check.computation = FALSE</code> , a character string saying “ <i>computation check was not requested</i> ”.
geodesic.chains.1	a data frame of the geodesic chains of the first kind.
geodesic.loops.1	a data frame of the geodesic loops of the first kind.
graph.lengths.of.geodesic.chains.1	a matrix of the graph-theoretic (edge/link based) lengths of the geodesic chains of the first kind.

graph.lengths.of.geodesic.loops.1
 a matrix of the graph-theoretic (edge/link based) lengths of the geodesic loops of the first kind.

geodesic.chains.2
 a data frame of the geodesic chains of the second kind.

geodesic.loops.2
 a data frame of the geodesic loops of the second kind.

graph.lengths.of.geodesic.chains.2
 a matrix of the graph-theoretic (edge/link based) lengths of the geodesic chains of the second kind.

graph.lengths.of.geodesic.loops.2
 a matrix of the graph-theoretic (edge/link based) lengths of the geodesic loops of the second kind.

S.index
 the same as in case of short computation; see above. (last component of long computation list)

Author(s)

Thomas Kiefer, Ali Uenlue. Based on original MATLAB source by Ehtibar N. Dzhafarov.

References

Dzhafarov, E. N. and Colonius, H. (2006) Reconstructing distances among objects from their discriminability. *Psychometrika*, **71**, 365–386.

Dzhafarov, E. N. and Colonius, H. (2007) Dissimilarity cumulation theory and subjective metrics. *Journal of Mathematical Psychology*, **51**, 290–304.

Uenlue, A. and Kiefer, T. and Dzhafarov, E. N. (2009) Fechnerian scaling in R: The package **fechner**. *Journal of Statistical Software*, **31**(6), 1–24. URL <https://www.jstatsoft.org/article/view/v031i06>.

See Also

[check.data](#) for checking data format; [check.regular](#) for checking regular minimality/maximality; [plot.fechner](#), the S3 method for plotting objects of the class fechner; [print.fechner](#), the S3 method for printing objects of the class fechner; [summary.fechner](#), the S3 method for summarizing objects of the class fechner, which creates objects of the class summary.fechner; [print.summary.fechner](#), the S3 method for printing objects of the class summary.fechner. See also [fechner-package](#) for general information about this package.

Examples

```
##
## (1) examples based on dataset morse
##

## dataset morse satisfies regular maximality in canonical form
morse
check.regular(morse, type = "percent.same")
```

```

## a self-contained 10-code subspace consisting of the codes for the
## letter B and the digits 0, 1, 2, 4, ..., 9
indices <- which(is.element(names(morse), c("B", c(0, 1, 2, 4:9))))
f.scal.morse <- fechner(morse, format = "percent.same")
f.scal.morse$geodesic.loops[indices, indices]
morse.subspace <- morse[indices, indices]
check.regular(morse.subspace, type = "percent.same")

## since the subspace is self-contained, results must be the same
f.scal.subspace.mo <- fechner(morse.subspace, format = "percent.same")
identical(f.scal.morse$geodesic.loops[indices, indices],
          f.scal.subspace.mo$geodesic.loops)
identical(f.scal.morse$overall.Fechnerian.distances[indices, indices],
          f.scal.subspace.mo$overall.Fechnerian.distances)

## Fechnerian scaling analysis using short computation
f.scal.subspace.mo
str(f.scal.subspace.mo)
attributes(f.scal.subspace.mo)
## for instance, the S-index
f.scal.subspace.mo$S.index

## Fechnerian scaling analysis using long computation
f.scal.subspace.long.mo <- fechner(morse.subspace,
                                  format = "percent.same",
                                  compute.all = TRUE,
                                  check.computation = TRUE)

f.scal.subspace.long.mo
str(f.scal.subspace.long.mo)
attributes(f.scal.subspace.long.mo)
## for instance, the geodesic chains of the first kind
f.scal.subspace.long.mo$geodesic.chains.1

## check whether the overall Fechnerian distance of the first kind is
## equal to the overall Fechnerian distance of the second kind
## the difference, by theory a zero matrix
f.scal.subspace.long.mo$check[1]
## or, up to machine precision
f.scal.subspace.long.mo$check[2]

## plot of the S-index versus the overall Fechnerian distance
## for all (off-diagonal) pairs of stimuli
plot(f.scal.subspace.long.mo)
## for all (off-diagonal) pairs of stimuli with geodesic loops
## containing at least 3 links
plot(f.scal.subspace.long.mo, level = 3)

## corresponding summaries, including Pearson correlation and C-index
summary(f.scal.subspace.long.mo)
## in particular, accessing detailed summary through assignment
detailed.summary.mo <- summary(f.scal.subspace.long.mo, level = 3)
str(detailed.summary.mo)

```

```

##
## (2) examples based on dataset wish
##

## dataset wish satisfies regular minimality in canonical form
wish
check.regular(wish, type = "probability.different")

## a self-contained 10-code subspace consisting of S, U, W, X,
## 0, 1, ..., 5
indices <- which(is.element(names(wish), c("S", "U", "W", "X", 0:5)))
f.scal.wish <- fechner(wish, format = "probability.different")
f.scal.wish$geodesic.loops[indices, indices]
wish.subspace <- wish[indices, indices]
check.regular(wish.subspace, type = "probability.different")

## since the subspace is self-contained, results must be the same
f.scal.subspace.wi <- fechner(wish.subspace,
                             format = "probability.different")
identical(f.scal.wish$geodesic.loops[indices, indices],
          f.scal.subspace.wi$geodesic.loops)
identical(f.scal.wish$overall.Fechnerian.distances[indices, indices],
          f.scal.subspace.wi$overall.Fechnerian.distances)

## dataset wish transformed to percent-same format
check.data(100 - (wish * 100), format = "percent.same")

## Fechnerian scaling analysis using short computation
f.scal.subspace.wi
str(f.scal.subspace.wi)
attributes(f.scal.subspace.wi)
## for instance, the graph-theoretic lengths of geodesic loops
f.scal.subspace.wi$graph.lengths.of.geodesic.loops

## Fechnerian scaling analysis using long computation
f.scal.subspace.long.wi <- fechner(wish.subspace,
                                  format = "probability.different",
                                  compute.all = TRUE,
                                  check.computation = TRUE)

f.scal.subspace.long.wi
str(f.scal.subspace.long.wi)
attributes(f.scal.subspace.long.wi)
## for instance, the oriented Fechnerian distances of the first kind
f.scal.subspace.long.wi$oriented.Fechnerian.distances.1
## or, graph-theoretic lengths of chains and loops
identical(f.scal.subspace.long.wi$graph.lengths.of.geodesic.chains.1 +
          t(f.scal.subspace.long.wi$graph.lengths.of.geodesic.chains.1),
          f.scal.subspace.long.wi$graph.lengths.of.geodesic.loops.1)

## overall Fechnerian distances are not monotonically related to
## discrimination probabilities; however, there is a strong positive
## correlation
cor(as.vector(f.scal.wish$overall.Fechnerian.distances),

```

```

as.vector(as.matrix(wish))

## check whether the overall Fechnerian distance of the first kind is
## equal to the overall Fechnerian distance of the second kind
## the difference, by theory a zero matrix
f.scal.subspace.long.wi$check[1]
## or, up to machine precision
f.scal.subspace.long.wi$check[2]

## plot of the S-index versus the overall Fechnerian distance
## for all (off-diagonal) pairs of stimuli
plot(f.scal.subspace.long.wi)
## for all (off-diagonal) pairs of stimuli with geodesic loops
## containing at least 5 links
plot(f.scal.subspace.long.wi, level = 5)

## corresponding summaries, including Pearson correlation and C-index
summary(f.scal.subspace.long.wi)
## in particular, accessing detailed summary through assignment
detailed.summary.wi <- summary(f.scal.subspace.long.wi, level = 5)
str(detailed.summary.wi)

```

morse

Rothkopf's Morse Code Data

Description

Rothkopf's (1957) Morse code data of discrimination probabilities among 36 auditory Morse code signals for the letters A, B, \dots, Z and the digits $0, 1, \dots, 9$.

Usage

```
morse
```

Format

The morse data frame consists of 36 rows and 36 columns, representing the Morse code signals for the letters and digits $A, \dots, Z, 0, \dots, 9$ presented first and second, respectively. Each number, an integer, in the data frame gives the percentage of subjects who responded 'same' to the row signal followed by the column signal.

Details

Each signal consists of a sequence of dots and dashes. A chart of the Morse code letters and digits can be found at https://en.wikipedia.org/wiki/Morse_code.

Rothkopf's (1957) 36×36 Morse code data gives the same-different judgements of 598 subjects in response to the 36×36 auditorily presented pairs of Morse codes. Subjects who were not familiar with Morse code listened to a pair of signals constructed mechanically and separated by a pause of approximately 1.4 seconds. Each subject was required to state whether the two signals presented

were the same or different. Each number in the morse data frame is the percentage of roughly 150 subjects.

Note

The original *Rothkopf's (1957)* 36×36 dataset does not satisfy regular maximality. There are two maximal entries in row #2, of value 84, which are p_{BB} and p_{BX} . Following the argument in *Dzhafarov and Colonius (2006)*, a statistically compatible dataset is obtained by replacing the value of p_{BX} with 83 and leaving the rest of the data unchanged. The latter is the dataset accompanying the package `fechner`.

For typographic reasons, it may be useful to consider only a small subset of the stimulus set, best, chosen to form a ‘self-contained’ subspace: a geodesic loop for any two of the subset’s elements (computed using the complete dataset) is contained within the subset. For instance, a particular self-contained 10-code subspace of the 36 Morse codes consists of the codes for the letter *B* and the digits 0, 1, 2, 4, . . . , 9 (see `fechner`).

Source

Rothkopf, E. Z. (1957) A measure of stimulus similarity and errors in some paired-associate learning tasks. *Journal of Experimental Psychology*, **53**, 94–101.

References

- Dzhafarov, E. N. and Colonius, H. (2006) Reconstructing distances among objects from their discriminability. *Psychometrika*, **71**, 365–386.
- Dzhafarov, E. N. and Colonius, H. (2007) Dissimilarity cumulation theory and subjective metrics. *Journal of Mathematical Psychology*, **51**, 290–304.
- Uenlue, A. and Kiefer, T. and Dzhafarov, E. N. (2009) Fechnerian scaling in R: The package `fechner`. *Journal of Statistical Software*, **31**(6), 1–24. URL <https://www.jstatsoft.org/article/view/v031i06>.

See Also

`check.data` for checking data format; `check.regular` for checking regular minimality/maximality; `fechner`, the main function for Fechnerian scaling. See also `wish` for Wish’s Morse-code-like data, and `fechner-package` for general information about this package.

noRegMin

Artificial Data: Regular Minimality Violated

Description

Artificial data of fictitious ‘discrimination probabilities’ among 10 fictitious stimuli.

Usage

noRegMin

Format

The noRegMin data frame consists of 10 rows and 10 columns, representing the fictitious stimuli presented in the first and second observation area, respectively. Each number, a numeric, in the data frame is assumed to give the relative frequency of perceivers scoring ‘different’ to the row stimulus ‘followed’ by the column stimulus.

Note

This dataset is artificial and included for illustrating regular minimality being violated. It differs from the artificial data [regMin](#) only in the entry in row #9 and column #10.

References

- Dzhafarov, E. N. and Colonius, H. (2006) Reconstructing distances among objects from their discriminability. *Psychometrika*, **71**, 365–386.
- Dzhafarov, E. N. and Colonius, H. (2007) Dissimilarity cumulation theory and subjective metrics. *Journal of Mathematical Psychology*, **51**, 290–304.
- Uenlue, A. and Kiefer, T. and Dzhafarov, E. N. (2009) Fechnerian scaling in R: The package **fechner**. *Journal of Statistical Software*, **31**(6), 1–24. URL <https://www.jstatsoft.org/article/view/v031i06>.

See Also

[regMin](#) for the other artificial data satisfying regular minimality in non-canonical form; [check.data](#) for checking data format; [check.regular](#) for checking regular minimality/maximality; [fechner](#), the main function for Fechnerian scaling. See also [morse](#) for Rothkopf’s Morse code data, [wish](#) for Wish’s Morse-code-like data, and [fechner-package](#) for general information about this package.

Examples

```
## dataset noRegMin violates regular minimality
noRegMin
check.regular(noRegMin, type = "reg.minimal")
```

plot.fechner

Plot Method for Objects of Class fechner

Description

S3 method to plot objects of the class fechner.

Usage

```
## S3 method for class 'fechner'
plot(x, level = 2, ...)
```

Arguments

x	a required object of class fechner, obtained from a call to the function <code>fechner</code> .
level	an optional numeric, integer-valued and greater than or equal to 2, giving the level of comparison of the S -index and the overall Fechnerian distance G .
...	further arguments to be passed to or from other methods. They are ignored in this function.

Details

The `plot` method graphs the results obtained from Fechnerian scaling analyses. It produces a scatterplot of the overall Fechnerian distance G versus the S -index, with rugs added to the axes and jittered (`amount = 0.01` of noise) to accommodate ties in the S -index and G values. The diagonal line $y = x$ is for visual inspection of the deviations of the two types of values.

The level of comparison refers to the minimum number of links in geodesic loops. That is, choosing level n means that comparison involves only those S -index and G values that have geodesic loops containing not less than n links.

If there are no (off-diagonal) pairs of stimuli with geodesic loops containing at least `level` links (in this case a plot is not possible), `plot.fechner` stops with an error message.

Value

If the arguments `x` and `level` are of required types, and if there are (off-diagonal) pairs of stimuli with geodesic loops containing at least `level` links, `plot.fechner` produces a plot, and invisibly returns `NULL`.

Author(s)

Thomas Kiefer, Ali Uenlue. Based on original MATLAB source by Ehtibar N. Dzhafarov.

References

Dzhafarov, E. N. and Colonius, H. (2006) Reconstructing distances among objects from their discriminability. *Psychometrika*, **71**, 365–386.

Dzhafarov, E. N. and Colonius, H. (2007) Dissimilarity cumulation theory and subjective metrics. *Journal of Mathematical Psychology*, **51**, 290–304.

Uenlue, A. and Kiefer, T. and Dzhafarov, E. N. (2009) Fechnerian scaling in R: The package **fechner**. *Journal of Statistical Software*, **31**(6), 1–24. URL <https://www.jstatsoft.org/article/view/v031i06>.

See Also

`print.fechner`, the S3 method for printing objects of the class `fechner`; `summary.fechner`, the S3 method for summarizing objects of the class `fechner`, which creates objects of the class `summary.fechner`; `print.summary.fechner`, the S3 method for printing objects of the class `summary.fechner`; `fechner`, the main function for Fechnerian scaling, which creates objects of the class `fechner`. See also `fechner-package` for general information about this package.

Examples

```
## Fechnerian scaling of dataset wish
f.scal.wish <- fechner(wish)

## results are plotted for comparison levels 2 and 5
plot(f.scal.wish)
plot(f.scal.wish, level = 5)
```

print.fechner *Print Method for Objects of Class fechner*

Description

S3 method to print objects of the class fechner.

Usage

```
## S3 method for class 'fechner'
print(x, ...)
```

Arguments

x a required object of class fechner, obtained from a call to the function [fechner](#).
... further arguments to be passed to or from other methods. They are ignored in this function.

Details

The print method prints the main results obtained from Fechnerian scaling analyses, which are the overall Fechnerian distances and the geodesic loops.

Value

If the argument x is of required type, print.fechner prints the overall Fechnerian distances and the geodesic loops, and invisibly returns x.

Author(s)

Thomas Kiefer, Ali Uenlue. Based on original MATLAB source by Ehtibar N. Dzhafarov.

References

Dzhafarov, E. N. and Colonius, H. (2006) Reconstructing distances among objects from their discriminability. *Psychometrika*, **71**, 365–386.
Dzhafarov, E. N. and Colonius, H. (2007) Dissimilarity cumulation theory and subjective metrics. *Journal of Mathematical Psychology*, **51**, 290–304.
Uenlue, A. and Kiefer, T. and Dzhafarov, E. N. (2009) Fechnerian scaling in R: The package **fechner**. *Journal of Statistical Software*, **31**(6), 1–24. URL <https://www.jstatsoft.org/article/view/v031i06>.

See Also

[plot.fechner](#), the S3 method for plotting objects of the class fechner; [summary.fechner](#), the S3 method for summarizing objects of the class fechner, which creates objects of the class summary.fechner; [print.summary.fechner](#), the S3 method for printing objects of the class summary.fechner; [fechner](#), the main function for Fechnerian scaling, which creates objects of the class fechner. See also [fechner-package](#) for general information about this package.

Examples

```
## Fechnerian scaling of dataset wish
## overall Fechnerian distances and geodesic loops are printed
(f.scal.wish <- fechner(wish))
```

```
print.summary.fechner Print Method for Objects of Class summary.fechner
```

Description

S3 method to print objects of the class summary.fechner.

Usage

```
## S3 method for class 'summary.fechner'
print(x, ...)
```

Arguments

x	a required object of class summary.fechner, obtained from a call to the function summary.fechner (through generic function summary).
...	further arguments to be passed to or from other methods. They are ignored in this function.

Details

The print method prints the summary information about objects of the class fechner computed by [summary.fechner](#), which are the number of stimuli pairs used for comparison, a summary of the corresponding S -index values, a summary of the corresponding Fechnerian distance G values, the Pearson correlation, the C -index, and the comparison level. Specific summary information details such as individual stimuli pairs and their corresponding S -index and G values can be accessed through assignment (see ‘Examples’).

Value

If the argument x is of required type, print.summary.fechner prints the afore mentioned summary information in ‘Details’, and invisibly returns x.

Author(s)

Thomas Kiefer, Ali Uenlue. Based on original MATLAB source by Ehtibar N. Dzhafarov.

References

- Dzhafarov, E. N. and Colonius, H. (2006) Reconstructing distances among objects from their discriminability. *Psychometrika*, **71**, 365–386.
- Dzhafarov, E. N. and Colonius, H. (2007) Dissimilarity cumulation theory and subjective metrics. *Journal of Mathematical Psychology*, **51**, 290–304.
- Uenlue, A. and Kiefer, T. and Dzhafarov, E. N. (2009) Fechnerian scaling in R: The package **fechner**. *Journal of Statistical Software*, **31**(6), 1–24. URL <https://www.jstatsoft.org/article/view/v031i06>.

See Also

`plot.fechner`, the S3 method for plotting objects of the class fechner; `print.fechner`, the S3 method for printing objects of the class fechner; `summary.fechner`, the S3 method for summarizing objects of the class fechner, which creates objects of the class summary.fechner; `fechner`, the main function for Fechnerian scaling, which creates objects of the class fechner. See also `fechner-package` for general information about this package.

Examples

```
## Fechnerian scaling of dataset morse
## summary information about the Fechnerian scaling object are printed
## accessing detailed summary through assignment
(detailed.summary <- summary(fechner(morse, format = "percent.same")))
str(detailed.summary)
detailed.summary$pairs.used.for.comparison[3, ]
```

regMin

Artificial Data: Regular Minimality In Non-canonical Form

Description

Artificial data of fictitious ‘discrimination probabilities’ among 10 fictitious stimuli.

Usage

```
regMin
```

Format

The regMin data frame consists of 10 rows and 10 columns, representing the fictitious stimuli presented in the first and second observation area, respectively. Each number, a numeric, in the data frame is assumed to give the relative frequency of perceivers scoring ‘different’ to the row stimulus ‘followed’ by the column stimulus.

Note

This dataset is artificial and included for illustrating regular minimality in the non-canonical form. It differs from the artificial data `noRegMin` only in the entry in row #9 and column #10.

References

- Dzhafarov, E. N. and Colonius, H. (2006) Reconstructing distances among objects from their discriminability. *Psychometrika*, **71**, 365–386.
- Dzhafarov, E. N. and Colonius, H. (2007) Dissimilarity cumulation theory and subjective metrics. *Journal of Mathematical Psychology*, **51**, 290–304.
- Uenlue, A. and Kiefer, T. and Dzhafarov, E. N. (2009) Fechnerian scaling in R: The package **fechner**. *Journal of Statistical Software*, **31**(6), 1–24. URL <https://www.jstatsoft.org/article/view/v031i06>.

See Also

`noRegMin` for the other artificial data violating regular minimality; `check.data` for checking data format; `check.regular` for checking regular minimality/maximality; `fechner`, the main function for Fechnerian scaling. See also `morse` for Rothkopf's Morse code data, `wish` for Wish's Morse-code-like data, and `fechner-package` for general information about this package.

Examples

```
## dataset regMin satisfies regular minimality in non-canonical form
regMin
check.regular(regMin, type = "reg.minimal")
```

summary.fechner

Summary Method for Objects of Class fechner

Description

S3 method to summarize objects of the class `fechner`.

Usage

```
## S3 method for class 'fechner'
summary(object, level = 2, ...)
```

Arguments

<code>object</code>	a required object of class <code>fechner</code> , obtained from a call to the function <code>fechner</code> .
<code>level</code>	an optional numeric, integer-valued and greater than or equal to 2, giving the level of comparison of the S -index and the overall Fechnerian distance G .
<code>...</code>	further arguments to be passed to or from other methods. They are ignored in this function.

Details

The summary method outlines the results obtained from Fechnerian scaling analyses. It computes the Pearson correlation coefficient and the C -index (see Uenlue, Kiefer, and Dzhafarov (2009))

$$C = \frac{2 \sum (S - G)^2}{\sum S^2 + \sum G^2}$$

for specific (controlled by the argument level) stimuli pairs with their corresponding S -index and G values.

The level of comparison refers to the minimum number of links in geodesic loops. That is, choosing level n means that comparison involves only those S -index and G values that have geodesic loops containing not less than n links.

If there are no (off-diagonal) pairs of stimuli with geodesic loops containing at least level links (in this case a summary is not possible), summary.fechner stops with an error message.

The function summary.fechner returns an object of the class summary.fechner (see ‘Value’), for which a print method, print.summary.fechner, is provided. Specific summary information details such as individual stimuli pairs and their corresponding S -index and G values can be accessed through assignment (see ‘Examples’).

Value

If the arguments object and level are of required types, and if there are (off-diagonal) pairs of stimuli with geodesic loops containing at least level links, summary.fechner returns a named list, of the class summary.fechner, consisting of the following four components:

pairs.used.for.comparison	a data frame giving the pairs of stimuli (first variable stimuli.pairs) and their corresponding S -index (second variable S.index) and G (third variable Fechnerian.distance.G) values used for comparison.
Pearson.correlation	a numeric giving the value of the Pearson correlation coefficient if it exists, or a character string saying “ <i>Pearson’s correlation coefficient is not defined</i> ” if it does not exist.
C.index	a numeric giving the value of the C -index.
comparison.level	a numeric giving the level of comparison used.

Author(s)

Thomas Kiefer, Ali Uenlue. Based on original MATLAB source by Ehtibar N. Dzhafarov.

References

- Dzhafarov, E. N. and Colonius, H. (2006) Reconstructing distances among objects from their discriminability. *Psychometrika*, **71**, 365–386.
- Dzhafarov, E. N. and Colonius, H. (2007) Dissimilarity cumulation theory and subjective metrics. *Journal of Mathematical Psychology*, **51**, 290–304.

Uenlue, A. and Kiefer, T. and Dzhafarov, E. N. (2009) Fechnerian scaling in R: The package **fechner**. *Journal of Statistical Software*, **31**(6), 1–24. URL <https://www.jstatsoft.org/article/view/v031i06>.

See Also

`plot.fechner`, the S3 method for plotting objects of the class fechner; `print.fechner`, the S3 method for printing objects of the class fechner; `print.summary.fechner`, the S3 method for printing objects of the class summary.fechner; `fechner`, the main function for Fechnerian scaling, which creates objects of the class fechner. See also `fechner-package` for general information about this package.

Examples

```
## Fechnerian scaling of dataset wish
f.scal.wish <- fechner(wish)

## results are summarized for comparison levels 2 and 5
summary(f.scal.wish)
summary(f.scal.wish, level = 5)

## accessing detailed summaries through assignment
str(detailed.summary.l1 <- summary(f.scal.wish))
detailed.summary.l5 <- summary(f.scal.wish, level = 5)
detailed.summary.l5$pairs.used.for.comparison[1, ]

## to verify the obtained summaries
f.scal.wish$geodesic.loops
f.scal.wish$S.index
f.scal.wish$overall.Fechnerian.distances
```

wish

Wish's Morse-code-like Data

Description

Wish's (1967) Morse-code-like data of discrimination probabilities among 32 auditory Morse-code-like signals.

Usage

```
wish
```

Format

The wish data frame consists of 32 rows and 32 columns, representing the Morse-code-like signals (see ‘Details’) presented first and second, respectively. Each number, a numeric, in the data frame gives the relative frequency of subjects who responded ‘different’ to the row signal followed by the column signal.

Details

The 32 Morse-code-like signals in *Wish's (1967)* study were 5-element sequences $T_1P_1T_2P_2T_3$, where T stands for a tone (short or long) and P stands for a pause (1 or 3 units long). As in *Dzhafarov and Colonius (2006)*, the stimuli are labeled $A, B, \dots, Z, 0, 1, \dots, 5$, in the order they are presented in *Wish's (1967)* article.

Wish's (1967) 32×32 Morse-code-like data gives the same-different judgements of subjects in response to the 32×32 auditorily presented pairs of codes.

Note

The original *Wish's (1967)* 32×32 dataset does not satisfy regular minimality. There is the entry $p_{TV} = 0.03$, which is the same as p_{VV} and smaller than $p_{TT} = 0.06$. Following the argument in *Dzhafarov and Colonius (2006)*, a statistically compatible dataset is obtained by replacing the value of p_{TV} with 0.07 and leaving the rest of the data unchanged. The latter is the dataset accompanying the package `fechner`.

For typographic reasons, it may be useful to consider only a small subset of the stimulus set, best, chosen to form a 'self-contained' subspace: a geodesic loop for any two of the subset's elements (computed using the complete dataset) is contained within the subset. For instance, a particular self-contained 10-code subspace of the 32 Morse-code-like signals consists of $S, U, W, X, 0, 1, \dots, 5$ (see [fechner](#)).

Source

Wish, M. (1967) A model for the perception of Morse code-like signals. *Human Factors*, **9**, 529–540.

References

- Dzhafarov, E. N. and Colonius, H. (2006) Reconstructing distances among objects from their discriminability. *Psychometrika*, **71**, 365–386.
- Dzhafarov, E. N. and Colonius, H. (2007) Dissimilarity cumulation theory and subjective metrics. *Journal of Mathematical Psychology*, **51**, 290–304.
- Uenlue, A. and Kiefer, T. and Dzhafarov, E. N. (2009) Fechnerian scaling in R: The package `fechner`. *Journal of Statistical Software*, **31**(6), 1–24. URL <https://www.jstatsoft.org/article/view/v031i06>.

See Also

[check.data](#) for checking data format; [check.regular](#) for checking regular minimality/maximality; [fechner](#), the main function for Fechnerian scaling. See also [morse](#) for Rothkopf's Morse code data, and [fechner-package](#) for general information about this package.

Index

- * **Fechnerian data format**
 - check.data, 3
 - * **Fechnerian scaling**
 - fechner, 7
 - fechner-package, 2
 - * **attribute**
 - fechner, 7
 - * **classes**
 - fechner, 7
 - * **datasets**
 - morse, 13
 - noRegMin, 14
 - regMin, 19
 - wish, 22
 - * **discrete object sets**
 - fechner, 7
 - * **hplot**
 - plot.fechner, 15
 - * **manip**
 - check.data, 3
 - check.regular, 5
 - fechner, 7
 - * **methods**
 - plot.fechner, 15
 - print.fechner, 17
 - print.summary.fechner, 18
 - summary.fechner, 20
 - * **models**
 - fechner, 7
 - * **package**
 - fechner-package, 2
 - * **percent same data format**
 - check.data, 3
 - check.regular, 5
 - * **print**
 - plot.fechner, 15
 - print.fechner, 17
 - print.summary.fechner, 18
 - summary.fechner, 20
 - * **probability different data format**
 - check.data, 3
 - check.regular, 5
 - * **regular maximality**
 - check.regular, 5
 - * **regular minimality**
 - check.regular, 5
 - * **univar**
 - fechner, 7
 - summary.fechner, 20
 - * **utilities**
 - check.data, 3
 - check.regular, 5
- check.data, 2, 3, 5, 7, 8, 10, 14, 15, 20, 23
- check.regular, 2, 4, 5, 8, 10, 14, 15, 20, 23
- fechner, 2, 4, 7, 7, 14–20, 22, 23
- fechner-internal, 2
- fechner-package, 2
- morse, 2, 13, 15, 20, 23
- noRegMin, 2, 14, 20
- plot.fechner, 2, 8, 10, 15, 18, 19, 22
- print.fechner, 2, 8, 10, 16, 17, 19, 22
- print.summary.fechner, 2, 10, 16, 18, 18, 21, 22
- regMin, 2, 15, 19
- summary, 18
- summary.fechner, 2, 8, 10, 16, 18, 19, 20
- wish, 2, 14, 15, 20, 22